

WEIGHT ONLY
SCALE

PS




Cely PS-50

Cely
PS-70 I

Dimensions DATA IN mm

	PS-50	PS-70 I
A	235	230
B	240	300
C	130	130



Dimensions of the plate for the
2 models: L230 x W190 mm.



CELY
PS SERIES



LCD
SEGMENT
DISPLAY



INTERNAL
RECHARGEABLE
BATTERY



METROLOGICAL
VERIFICATION
OPTIONAL (EU) IN
PS-50 FOR SOME
CAPACITIES

Characteristics and functionality

Main characteristics

- Industrial weight only scale without printer.
- Valid for legal metrology (consult models).
- Battery:
 - › Up to 70 hours' runtime for all the models, depending on conditions of use.
- IP65 protection equivalent (only in Cely PS-70 I).

Features

- Weighing.
- Units' change.
- Auto power off.
- Tare.

Capacity / Accuracy

- Cely PS-50: 3 kg / 0.5 g, 3 kg / 1 g, 6 kg / 1 g, 6 kg / 2 g, 15 kg / 2 g or 15 kg / 5 g.
- Cely PS-70 I: 6 kg / 2 g or 15 kg / 5 g.

Models

Cely PS-50

RANGE 3 kg / 0.5 g

Ref.: **71AOPS500001UE**

RANGE 6 kg / 1 g

Ref.: **71AOPS500002UE**

RANGE 15 kg / 2 g

Ref.: **71AOPS500003UE**

(M) not available

RANGE 3 kg / 1 g

Ref.: **71AOPS500004UE**

RANGE 6 kg / 2 g

Ref.: **71AOPS500005UE**

RANGE 15 kg / 5 g

Ref.: **71AOPS500006UE**

(M) optional

Cely PS-70 I

RANGE 6 kg / 2 g

Ref.: **71APS70I0005UE**

RANGE 15 kg / 5 g

Ref.: **71APS70I0006UE**

(M) not available

Note:

- The references correspond to standard models: White ABS plastic or stainless steel casing, backlit LCD segment display and flat stainless steel plate.
- Capacity: Monorange, from 3 up to 15 kg.

Options

Option	Characteristics	Reference
Metrological verification (M)	According to EU weighing directives. (See section on equipment metrological verification).	Consult

Available formats

- Flat.

Construction

- Structure:
 - › PS-50: ABS plastic housing.
 - › PS-70 I: Stainless steel housing.
- Console:
 - › PS-50: Keypad with 3-keys and backlit LCD segment display of 5 digits (20 mm).
 - › PS-70 I: Keypad with 3-keys and backlit LCD segment display of 4 digits (25 mm).
- Plate:
 - › Material: Stainless steel.

Power supply

- Mains: AC (12 V / 500 mA) adaptor.
- Internal rechargeable battery:
 - › 6 V / 4 Ah in PS-50.
 - › 6 V / 3.2 Ah in PS-70 I.